

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets

(11) Veröffentlichungsnummer:

(11) Publication number:

(11) Numéro de publication:

EP 1 121 049 A0

Internationale Anmeldung veröffentlicht durch die
Weltorganisation für geistiges Eigentum unter der Nummer:

WO 00/21433 (art. 158 des EPÜ).

International application published by the World
Intellectual Property Organisation under number:

WO 00/21433 (art. 158 of the EPC).

Demande internationale publiée par l'Organisation
Mondiale de la Propriété sous le numéro:

WO 00/21433 (art. 158 de la CBE).

Best Available Copy

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

| | | |
|---|-----------|---|
| (51) International Patent Classification ⁶ : A61B 5/00 | A1 | (11) International Publication Number: WO 00/21433 (43) International Publication Date: 20 April 2000 (20.04.00) |
| (21) International Application Number: PCT/US99/21462 (22) International Filing Date: 15 October 1999 (15.10.99) (30) Priority Data: 60/104,332 15 October 1998 (15.10.98) US 09/289,647 12 April 1999 (12.04.99) US 09/417,898 14 October 1999 (14.10.99) US (71) Applicant: SENSIDYNE [US/US]; 16333 Bay Vista Drive, Clearwater, FL (US). (72) Inventor: PARKER, Brent; 39750 Naples Drive, Murrieta, CA 92563 (US). (74) Agent: ZEGER, Jim; 801 N. Pitt Street #108, Alexandria, VA 22314 (US). | | (81) Designated States: AU, BR, CA, JP, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i> <i>With amended claims.</i> |

(54) Title: REUSABLE PULSE OXIMETER PROBE AND DISPOSABLE BANDAGE APPARATUS

(57) Abstract

A reusable pulse oximeter sensor and disposable bandage apparatus includes: a) a reusable pulse oximeter probe assembly with at least one light-emitting diode and one photocell detector wherein the detector and emitter are enclosed in plastic housings, one housing having an aperture or radiation transparent window aligned with the emitter and the other housing having an aperture or radiation transparent window aligned with the detector; and b) a bandage strip having adhesive on at least a portion of at least one face thereof and at least two plastic receptacles mounted thereon, each receptacle having at least one aperture or radiation transparent window located therein; wherein the probe housings can matedly engage the bandage receptacles, and transmit and receive light through the apertures or radiation transparent windows of the mated housings and receptacles, and through the appendage of a patient.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

| | | | | | | | |
|----|--------------------------|----|--|----|--|----|--------------------------|
| AL | Albania | ES | Spain | LS | Lesotho | SI | Slovenia |
| AM | Armenia | FI | Finland | LT | Lithuania | SK | Slovakia |
| AT | Austria | FR | France | LU | Luxembourg | SN | Senegal |
| AU | Australia | GA | Gabon | LV | Latvia | SZ | Swaziland |
| AZ | Azerbaijan | GB | United Kingdom | MC | Monaco | TD | Chad |
| BA | Bosnia and Herzegovina | GE | Georgia | MD | Republic of Moldova | TG | Togo |
| BB | Barbados | GH | Ghana | MG | Madagascar | TJ | Tajikistan |
| BE | Belgium | GN | Guinea | MK | The former Yugoslav Republic of Macedonia | TM | Turkmenistan |
| BF | Burkina Faso | GR | Greece | ML | Mali | TR | Turkey |
| BG | Bulgaria | HU | Hungary | MN | Mongolia | TT | Trinidad and Tobago |
| BJ | Benin | IE | Ireland | MR | Mauritania | UA | Ukraine |
| BR | Brazil | IL | Israel | MW | Malawi | UG | Uganda |
| BY | Belarus | IS | Iceland | MX | Mexico | US | United States of America |
| CA | Canada | IT | Italy | NE | Niger | UZ | Uzbekistan |
| CF | Central African Republic | JP | Japan | NL | Netherlands | VN | Viet Nam |
| CG | Congo | KE | Kenya | NO | Norway | YU | Yugoslavia |
| CH | Switzerland | KG | Kyrgyzstan | NZ | New Zealand | ZW | Zimbabwe |
| CI | Côte d'Ivoire | KP | Democratic People's Republic of Korea | PL | Poland | | |
| CM | Cameroon | KR | Republic of Korea | PT | Portugal | | |
| CN | China | KZ | Kazakstan | RO | Romania | | |
| CU | Cuba | LC | Saint Lucia | RU | Russian Federation | | |
| CZ | Czech Republic | LI | Liechtenstein | SD | Sudan | | |
| DE | Germany | LK | Sri Lanka | SE | Sweden | | |
| DK | Denmark | LR | Liberia | SG | Singapore | | |
| EE | Estonia | | | | | | |

**REUSABLE PULSE OXIMETER PROBE
AND DISPOSABLE BANDAGE APPARATUS**

REFERENCE TO RELATED APPLICATION

This application is a continuation-in-part of patent application Serial No. 09/289,647 filed April 12, 1999 and entitled REUSABLE PULSE OXIMETER PROBE AND DISPOSABLE
5 BANDAGE APPARATUS, which in turn is a nonprovisional application of provisional application Serial No. 60/104,332 filed October 15, 1998.

BACKGROUND OF THE INVENTION

Heretofore the use of pulse oximeter probes has been
10 limited to the use of a costly reusable probe, which is contaminated by use on a patient, or cheaper, single-use probes, which, in the aggregate, amount to a considerable expenditure for a health care institution. The present invention relates to a method of making and affixing a
15 reusable probe to a patient by means of disposable bandage apparatus so that there is no contact between the costly, reusable portion of the probe and the patient. The contaminated bandage apparatus, which is relatively inexpensive, can then be discarded after single patient use
20 and the probe can be reused with a new bandage apparatus.

Others have attempted to convert single-use probes into multi-use probes through a lamination process. In that process, the original adhesive material is removed from the original manufacturer's sensor. The sensor is then laminated in a plastic sheath and the entire sheath is then inserted into a transparent, adhesive-backed sleeve, which is then adhered to a patient. After use, the probe can then be extracted from the sleeve and inserted into a new sleeve for use on another patient.

There are certain disadvantages to this method. Firstly, it is difficult to insert the flexible laminated sensor into a long sleeve. Secondly, the thickness of a laminated sensor inside of a sleeve makes it difficult to bend around, and to stick properly to, a human appendage. Thirdly, transmission and reception of infrared light can be affected by extraneous light entering from the sides of the sleeve. And, Fourthly, there is some dispute as to the affect on infrared light transmission when passing through the sleeve and the adhesive material coupled thereto.

THE PRESENT INVENTION

The present invention not only solves the problems outlined above, but offers an alternative that is cheap to manufacture and easy to use.

In detail, the present invention is a method for improving the form and affixation method of a reusable pulse oximeter sensor. It comprises a reusable pulse

oximeter probe with at least one light-emitting diode and one photocell detector wherein the emitter and detector are enclosed in plastic housings, one housing having an aperture or radiation transparent window aligned with the emitter, and the other housing having an aperture or radiation transparent window aligned with the detector. Also included is a disposable bandage apparatus which is a bandage strip having adhesive on at least a portion of at least one face thereof and at least two plastic receptacles mounted thereon, each receptacle having at least one aperture or radiation transparent window located therein. The probe housings can matedly engage the bandage receptacles and transmit and receive light through the apertures or radiation transparent windows of the mated housings and receptacles, and through the appendage of a patient. The apertures of the receptacles are large enough to accept the tubular protrusions of the housings for the purpose of concentric location and alignment of the housings to the receptacles and the proper transmission and reception of light therethrough. Sandwiched between the adhesive strip and the receptacles attached thereto, are translucent silicone windows or windows of another radiation transparent material for isolation of the reusable probe assembly from the patient. The bandage apparatus may be discarded after single patient use and the reusable probe may be used again on another patient in conjunction with another bandage apparatus. Additionally,

the receptacles of the bandage apparatus may have a concave surface on one side thereof in order to seat conformably on a human digit, or they have a flat surface on at least one side thereof in order to attach conformably to a human foot, nose, or ear. The housings and receptacles also contain "mushroom hook" type hook and loop material for the purpose of adhering and detaching the housings to and from the receptacles. Additionally, the housings and receptacles have recessed areas for adhesion of the "mushroom hook" hook and loop material.

In another embodiment of the invention, the receptacle of the disposable bandage apparatus may be the mushroom hook material itself which may be attached directly to the adhesive strip for the selective engagement of the housings of the probe assembly.

Finally, and in the preferred embodiment of the invention, the light-emitting diode and photocell detector of the probe assembly may be mounted in modular housings with locking levers which can engage an indentation or slot in the receptacles and securely lock the housings into proper position within the receptacles, thus allowing the transmission and reception of infrared light through the mated housings and receptacles and through the appendage of a patient. In this embodiment, the silicone, or other radiation transparent windows, may be mounted against the skin of a patient, and may be used to secure the receptacles on the opposite side of the bandage strip.

This is accomplished by the use of locking levers which are pushed through holes or slots in the bandage and engage the receptacles mounted on the opposite side of the bandage, thus sandwiching the bandage in between.

5 **DESCRIPTION OF THE DRAWINGS**

The above and other advantages of the invention will become more clear when considered with the following specification and accompanying drawings wherein:

10 Figure 1 is an exploded view of the reusable pulse oximeter probe and disposable bandage apparatus incorporating the invention;

Figure 2 is a view of the reusable pulse oximeter probe and disposable bandage apparatus shown individually as components of the invention;

15 Figure 3 illustrates the invention in use on a human finger or digit;

Figure 4 illustrates an exploded view of another embodiment of the invention in which the "mushroom hook" material itself is used as the receptacle of the disposable
20 bandage apparatus;

Figure 5 illustrates an assembled view of the preferred embodiment of the reusable pulse oximeter sensor in which the light-emitting diode and photocell detector of the reusable probe are mounted in modular housings with
25 locking levers;

Figure 6 illustrates an exploded view of the preferred embodiment of the reusable pulse oximeter sensor;

Figure 7 illustrates an exploded view of the preferred embodiment of the bandage apparatus in which the receptacle
5 tops incorporate a slot for engaging the locking levers of the modular probe housings, and wherein the radiation transparent windows are mounted on the opposite side of the bandage strip thus sandwiching and securing the bandage in
10 between the two receptacle halves by means of locking levers; and

Figure 8 illustrates the preferred embodiment of the invention as it would appear ready for use on a human digit.

Description of the Reusable Pulse Oximeter Sensor

15 The reusable pulse oximeter sensor constitutes a "Y" style pulse oximeter probe shown in Figure 1, Item F. The probe incorporates two plastic housings shown as Figure 1, Items G. The housings contain apertures or radiation transparent windows L therein. One housing contains the
20 light-emitting diode of the probe, Figure 1, item H, and other contains the photocell detector, Figure 1, Item I. The emitter and detectors are aligned with the apertures or windows L of the housings in order to transmit and receive light through a human appendage.

25 Seated within a recessed area of each housing, and attached permanently thereto, is a "mushroom hook"

adhesive-backed pad, Figure 1, Item K. The purpose of these pads is to selectively engage the "mushroom hook" pads, Figure 1, Items J, attached permanently to the plastic discs, Figure 1, Items D, and to attach the reusable probe assembly to the Disposable Bandage Apparatus. The reusable pulse oximeter sensor is shown assembled as Figure 2, Item A.

In the preferred embodiment of the reusable pulse oximeter sensor, the light-emitting diode (Figure 5, Item A) and photocell detector (Figure 5, Item B) of the probe assembly are housed in modular receptacles (Figure 5, Items C) having locking levers (Figure 5, Items D) for engaging the receptacles of the disposable bandage apparatus, and locking them into place. In this embodiment, the light-emitting diode (Figure 6, Item A) and the photocell detector (Figure 6, Item B) are sandwiched between interlocking receptacle halves, the bottom halves of which (Figure 6, Items C) are made of a radiation transparent material.

Description of the Disposable Bandage Apparatus

The components of the apparatus include an adhesive-backed strip, shown as Figure 1, Item A, the strip A incorporating two oval protrusions B centered thereon and shown as Figure 1. The strip also incorporates two apertures, centrally located within the oval protrusions, each aperture C having a diameter sufficient in size to

accommodate the transmission and reception of light from a light-emitting diode and photocell detector of a pulse oximeter probe.

On top of the apertures C are seated two plastic discs, Figure 1, Item D, each having a concave base designed to conform to the radius of a human digit, and an aperture of slightly larger diameter than the apertures in the adhesive backed planar strip. The plastic discs are affixed to the adhesive planar strip by means of a permanent adhesive.

Seated in a recessed area on top of each plastic disc is a "mushroom hook", adhesive backed pad shown as Figure 1, Item J. The purpose of the "mushroom hook" pads is to selectively engage the "mushroom hook" pads attached to the probe, Figure 1, Items K, and to attach the probe to the disposable bandage apparatus. Sandwiched between the two plastic discs and the planar adhesive strip are two translucent silicone windows, Figure 1, Item E. The windows are designed to permit the passage of infrared light and yet prevent contact between probe and patient, and consequently, contamination of the reusable probe itself.

The above items constitute the disposable bandage apparatus of the invention, the apparatus being shown assembled as Figure 2, Item B.

In another embodiment of the invention, the disposable bandage apparatus may be configured as in Figure 4 of the

drawings. Figure 4 is an exploded view of the apparatus in which the "mushroom hook" pads of the bandage apparatus, Figure 4, Items J, are bonded directly to the adhesive planar strip, Figure 4, Item A, for the selective engagement of the "mushroom hook" pads of the probe, Figure 4, Items K, the pads being attached permanently to the housings of the probe, Figure 4, Items G.

In the preferred embodiment of the disposable bandage apparatus, the bandage strip (Figure 7, Item A) is sandwiched between interlocking receptacle halves. The top halves of the receptacles (Figure 7, Items B) contain locking levers (Figure 7, Items C) that are pushed through slots cut in the bandage strip (Figure 7, Items D) and lockingly engage indentations (Figure 7, Items E) in the bottom halves of the receptacles (Figure 7, Items F), thus sandwiching and locking the bandage in between. The bandage strip contains two apertures (Figure 7, Items G) for the transmission and reception of light from the light-emitting diode and photocell detector of the pulse oximeter sensor which are encased in modular housings having locking levers (Figure 5, Items D) wherein the levers engage slots in the receptacles (Figure 7, Items H) thereby locking the housings into place within the receptacles. In addition, the bottom halves of the receptacles (Figure 7, Items F) are of a radiation transparent material, thus allowing the light-emitting diode and photocell detector contained in the probe housings, when engaged in the bandage

receptacles, to transmit and receive light through the apertures of the bandage strip and through the radiation transparent material of the bottom halves of the receptacles, and through the appendage of a patient. The complete reusable pulse oximeter probe and bandage assembly is shown assembled and ready for use on a human digit in Figure 8.

Other Fastening Means

As can be appreciated, there are many ways of fabricating the above components of the invention. The above description describes attachment of the reusable pulse oximeter sensor to the disposable bandage apparatus by way of a "mushroom hook" type hook and loop material and by the use of telephone type modular connectors and receptacles. In addition to this means, a number of other methods may be used including standard hook and loop material, "ring and groove" type snap-on connectors, "push and twist" type Luerlock connectors, and threaded flange type connectors.

Method of Use

For use on each individual patient, the probe is affixed in the following manner:

Firstly, the backing is removed from the adhesive strip of the disposable bandage apparatus. One of the apertures of the apparatus is visually positioned on the

center of the nail bed of the patient's appendage and one side of the adhesive strip and the oval protrusions are adhered to the patient's digit. The rest of the strip is then looped over the end of the patient's appendage, and the plastic disc is aligned so as to exactly oppose the plastic disc already attached to the other side of the digit. Once the disposable bandage apparatus has been properly adhered to the patient, the plastic housings of the probe assembly can be easily snapped into place on opposing sides of the digit. The entire assembled probe is shown as it would appear in use on a patient in Figure 3.

For use with each patient, the modular probe and bandage assembly, which is the preferred embodiment of the invention, would be attached as follows:

Firstly, the backing is removed from the adhesive strip. The strip is then folded where indicated on the bandage and the strip is then adhered to opposing sides of the human digit. Once the bandage apparatus is in place, the housings of the probe are pushed into the receptacles and locked in place by means of the locking levers.

In all embodiments of the invention, when the probe is no longer required on the patient, the housings of the reusable probe are simply unsnapped from the disposable bandage apparatus, the bandage apparatus is thrown away, and the probe can then be reused on a new patient in conjunction with a new bandage apparatus.

ADVANTAGES OF THE PRESENT INVENTION

• Current reusable pulse oximeter probes are either "clam shell" type clamping devices which can restrict circuit or "Y" type probes which are taped directly to the patient. Both types also come in direct contact with the patient's skin and bodily fluids and need sterilization after use. Because of the fact that these devices incorporate many surfaces and at times, porous materials, proper sterilization is very difficult. With the present invention there is no contact between the reusable probe and the skin or bodily fluids of the patient.

• Disposable probes are very costly because of the fact that the cable, connectors and photodiodes are all disposed of after use. the present invention accomplishes the same goals as a disposable probe from a cleanliness standpoint, but since only the attachment apparatus is discarded after use, the cost is much less to a healthcare institution.

• The present invention, with the concave shape of the plastic discs of the bandage apparatus, when backed by the adhesive strip, is extremely effective in preventing the entrance of extraneous light from the sides of the patient's digit. Current probes on the market, whether disposable or reusable, because of the nature of their shape and affixation means, have problems in dealing with extraneous light reception.

• The present invention utilizes an easy snap-on, snap-off, or modular connector attachment means for attaching

the probe to the disposable bandage apparatus. Probe-shield type devices available in the past not only required the modification of the original manufacturer's probe, but required the difficult procedure of inserting a flexible laminated probe into a sheath for each patient.

- Probe-shield devices, because of the lamination process involved, raised some concern over the transmission and reception of infrared light through the laminating material. The present invention uses a silicone window for the isolation of the probe from the patient. Infrared light transmission and reception is not affected by passage through translucent silicone.

- In these days of environmental consciousness, the annual waste generated from tens of millions of disposable probes is enormous. The present invention, if used in considerable numbers, would greatly reduce the amount of environmental waste generated by disposable pulse oximeter probes.

While the invention has been described in relation to preferred embodiments of the invention, it will be appreciated that other embodiments, adaptations and modifications of the invention will be apparent to those skilled in the art.

WHAT IS CLAIMED IS:

1. A reusable pulse oximeter sensor and disposable bandage apparatus, comprising:

a) a reusable pulse oximeter probe assembly with at least one light-emitting diode and one photocell detector wherein said detector and emitter are enclosed in plastic housings one housing having an aperture or radiation transparent window aligned with said emitter and the other housing having an aperture or radiation transparent window aligned with said detector;

b) a bandage strip having adhesive on at least a portion of at least one face thereof and at least two plastic receptacles mounted thereon, each receptacle having at least one aperture or radiation transparent window located therein;

wherein said probe housings can matedly engage said bandage receptacles, and transmit and receive light through the apertures or radiation transparent windows of said mated housings and receptacles, and through the appendage of a patient.

2. The reusable pulse oximeter sensor and disposable bandage of Claim 1 wherein translucent silicone or other radiation transparent windows are sandwiched between said adhesive strip, and said receptacles attached thereto.

3. The reusable pulse oximeter sensor and disposable bandage of Claim 1 wherein the apertures of said receptacles are large enough to accept the tubular protrusions of said housings for the purpose of concentric location of the housings to the receptacles and the proper transmission of light therethrough.

4. The reusable pulse oximeter sensor and disposable bandage of Claim 1 wherein said bandage apparatus may be discarded after single patient use and said reusable probe may be used again on another patient in conjunction with a new bandage apparatus.

5. The reusable pulse oximeter sensor and disposable bandage of Claim 1 wherein said receptacles have a concave shape on one side thereof in order to seat conformably on a human digit.

6. The reusable pulse oximeter sensor and disposable bandage of Claim 1 wherein said receptacles have a flat surface on at least one side thereof in order to seat conformably on a human ear, nose, or foot.

7. The reusable pulse oximeter sensor and disposable bandage of Claim 1 wherein the housings and receptacles contain "mushroom hook" type hook and loop material for the

purpose of adhering and detaching said housings to and from said receptacles.

8. The reusable pulse oximeter sensor and disposable bandage of Claim 1 wherein the housings and receptacles have recessed areas for adhesion of the "mushroom hook" hook and loop material.

9. The reusable pulse oximeter sensor and disposable bandage of Claim 1 wherein the receptacles of said disposable bandage are the "mushroom hook" material itself.

10. The reusable pulse oximeter sensor of Claim 1 wherein said light-emitting diode and said photocell detector are mounted in modular housings having locking levers.


11. The disposable bandage of Claim 1 wherein the receptacles mounted thereon can matedly engage modular housings with locking levers, said receptacles having a notch, slot or indentation therein whereby at least a portion of said locking levers can lodge therein, thus locking and securing said housings to said receptacles.

12. The bandage of Claim 1 wherein at least a portion of said plastic receptacles themselves constitute said radiation transparent windows.

13. A method for improving the affixation of a reusable pulse oximeter sensor wherein a planar adhesive strip with at least two apertures therein, and plastic receptacles mounted on top of said apertures, may be visually aligned on the digit of a patient by looking through said first aperture in order to attach said first aperture over the nail bed of a patient, prior to the engagement of the reusable probe in said receptacle.


1/8

FIGURE 1




2/8

FIGURE 2




3/8

FIGURE 3




4/8

FIGURE 4




5/8

FIGURE 5




6/8

FIGURE 6




7/8

FIGURE 7



8/8

FIGURE 8



INTERNATIONAL SEARCH REPORT

International application No.
PCT/US99/21462

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) : A61B 5/00

US CL : 600/344

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 600/310, 322, 323, 340, 344

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

| Category* | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. |
|-----------|--|-----------------------|
| A, P | US 5,879,373 A (ROPER et al.) 09 March 1999, entire document. | 1-12 |
| X | US 5,090,410 A (SAPER et al.) 25 February 1992, entire document. | 13 |

☐ Further documents are listed in the continuation of Box C.

☐ See patent family annex.

| | |
|---|--|
| * Special categories of cited documents: | *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention |
| *A* document defining the general state of the art which is not considered to be of particular relevance | *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone |
| *B* earlier document published on or after the international filing date | *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art |
| *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) | *Z* document member of the same patent family |
| *O* document referring to an oral disclosure, use, exhibition or other means | |
| *P* document published prior to the international filing date but later than the priority date claimed | |

Date of the actual completion of the international search

30 DECEMBER 1999

Date of mailing of the international search report

04 FEB 2000

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

ERIC F. WINAKUR

Telephone No. (703) 308-3940

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☒ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.